



Material Safety Data Sheet

Material Name: Medium Curing Cutback

Section 1: CHEMICAL PRODUCT and COMPANY IDENTIFICATION

Manufacturer Information:

Colasphalt, a division of Canadian Road Builders Inc.
Zone 4, 26222 Twp Rd 530A
Acheson, Alberta, T7X 5A7

Contact information

Phone: (780) 960-3423
Fax: (780) 960-1666




Product Name:

Medium Curing Cutback Asphalt

Product Identifiers:

MC-30, MC-70, MC-250, MC-800, MC-3000

Section 2: HAZARD IDENTIFICATION

WHIMIS		TDG	
	Class B: Combustible Material		UN 1999 Class 3 PG III Tars and Liquids
	Class D, Division 2 Poisonous Material		

Emergency Overview

Combustible liquid and vapor. Hot product will cause severe burns. If burned by hot product, cool affected area immediately with cold water. Do not remove asphalt cement from skin. Heated product may release toxic hydrogen sulfide. Repeated or prolonged contact with skin can produce irritation or dermatitis.

Potential Health Effects – Eyes

Vapors are irritating to the eyes. Hot liquid asphalt may cause serious thermal burns on direct contact. Any exposure to the eyes requires immediate first aid attention.

Potential Health Effects – Skin

Hot liquid product may cause serious thermal burns on direct contact. Any prolonged skin contact can result in dry cracked skin and dermatitis.

Potential Health Effects – Ingestion

Not a likely route of exposure under normal product use conditions. Do not ingest asphalt. Hot product will cause thermal burns.



Material Safety Data Sheet

Material Name: Medium Curing Cutback

Potential Health Effects – Inhalation

May Cause headaches, dizziness and loss of appetite. Product vapors may be irritating to the respiratory tract, nose and throat. Hydrogen sulfide and other sulfur containing gasses may be present at elevated temperatures. Effects of exposure could include irritation to the nose and throat, nausea, vomiting and signs of nervous system depression.

Section 3: COMPOSITION/INFORMATION on INGREDIENTS

Component	Percent (w/w)	CAS Number	LD ₅₀	LC ₅₀
Asphalt Cement	60-95	8052-42-4	Oral 5000 mg/kg Dermal 2000 mg/kg	N/A
Kerosene Distillate	5-40	8008-20-6	Oral 2835 mg/kg (rabbit) Dermal 2000 mg/kg (rabbit)	5000 mg/m ³ (rat), 4H

Section 4: FIRST AID MEASURES

First Aid – Eyes

Flush eyes for at least 15 minutes with clean water. Patch lightly, allowing drainage. Seek medical attention.

First Aid – Skin

Remove non-adhering contaminated clothing. Cool adherent materials and burned areas with ice and/or cold water. Do not remove adherent material or clothing. Do not use solvents to remove asphalt from the skin. Seek medical attention.

First Aid – Ingestion

Do not induce vomiting or give liquids. Seek immediate medical attention.

First Aid – Inhalation

Move exposed person to fresh air. If breathing has stopped, apply artificial respiration. Seek medical attention.

Section 5: FIRE FIGHTING MEASURES

General Fire Hazards

See Section 9 for Flammability properties.

Combustible liquid according to WHMIS criteria. Release vapors may form flammable/explosive concentrations in confined areas.

Hazardous Combustion Products

Toxic gases produced in fire, such as CO, CO₂, and H₂S.

Extinguishing Media

Use dry chemical foam or CO₂.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear



Material Safety Data Sheet

Material Name: Medium Curing Cutback

Section 6: ACCIDENTAL RELEASE MEASURES

Containment Procedures

Eliminate all sources of ignition. Contain hot liquid by diking and allow to cool and solidify.

Clean-Up Procedures

Comply with federal, provincial and local requirements for spill notification.

Evacuation Procedures

Isolate area. Keep unnecessary personnel away.

Special Procedures

Wear appropriate protective equipment and clothing during clean-up.

Section 7: HANDLING AND STORAGE

Handling Procedures

Grounding of containers/pouring equipment is necessary when transferring hot liquid product. Significant concentrations of hydrogen sulfide (H₂S) gas can be generated and accumulate in storage tanks and bulk transport compartments which may require additional precautions and procedures during loading and unloading. When opening covers and outlet caps on storage tanks, use face shield and gloves to avoid possible injury from pressurized product.

Storage Procedures

Store product below the flash point and keep away from all ignition sources. Head spaces in storage tanks may contain toxic hydrocarbon vapors and hydrogen sulphide gas.

Section 8: EXPOSURE CONTROLS AND PERSONEL PROTECTION

Component Exposure Limits

Asphalt (CAS #: 8052-42-4)

ACGIH: 0.5 mg/m³ TWA (fume, inhalable fraction, as benzene soluble aerosol)

NIOSH: 5 mg/m³ Ceiling (15 min, fumes)

Kerosene Distillate (CAS #: 8008-20-6)

ACGIH: 200 mg/m³ TWA (skin, Application restricted to conditions in which there are negligible aerosol exposures)

Engineering Controls:

Use local exhaust or general dilution ventilation when using at elevated temperatures or during activities that generate vapors or mists, to maintain levels below exposure limits. Ensure that an emergency eye wash station and safety shower is located near the work area.

Personal Protective Equipment (PPE):

Respiratory Protection:

Use air purifying respirators with organic vapor cartridges in poorly ventilated areas and at product temperatures of 185° or greater. At elevated concentrations exceeding 10x the exposure limit use air supplied respirators or self-contained breathing apparatus.

Eye Protection:

Wear approved safety goggles or face shield when handling asphalt cement to prevent contact with eyes.



Material Safety Data Sheet

Material Name: Medium Curing Cutback

Skin Protection:

Wear chemical resistant gloves (e.g. neoprene or butyl rubber) to prevent skin contact and insulated gloves when handling hot product. Additional protection may be necessary to prevent skin contact including use of apron, arm covers, face shield or boots.

Section 9: PHYSICAL and CHEMICAL PROPERTIES

Physical State: Black highly viscous

Appearance: Black, viscous

Flash Point: 49°C

Auto Ignition Temperature: 370°C

Lower Flamability limit: N/A

Odor: Slight petroleum odor.

Vapor Pressure: N/A

Vapor Density: 4.5 (approx.) @ 20°C

Specific Gravity: 0.94 -1.02

Evaporation Rate: Slow.

pH (in water): N/A

Flash Point Method: N/A

Upper Flamability Limit: N/A

Octanal/H₂O Coeff: N/A

Boiling Point: 169°C

Freezing Point: N/A

Viscosity: 30-3000 cSt at 60°C

Solubility in Water: insoluble

Section 10: CHEMICAL STABILITY & REACTIVE INFORMATION

Chemical Stability

Stable. Avoid contact with incompatible materials, excessive heat, sources of ignition and open flame.

Chemical Stability: Conditions to Avoid

None

Incompatibility

Incompatible with strong acids or bases, and oxidizing agents such as nitrates, chlorates and peroxides.

Hazardous Decomposition

Oxides of carbon, sulfur and nitrogen. Styrene, 1, 3 butadiene and aldehydes.

Possibility of Hazardous Reactions

Will not occur.

Section 11: TOXICOLOGICAL and ECOLOGICAL INFORMATION

Carcinogenicity

Hazardous by OSHA/WHMIS criteria, May cause cancer. Long-term or repeated exposures to asphalt fumes are possibly carcinogenic to humans. Kerosene has shown the potential to cause skin cancer in laboratory animals when applied over the life time of the animal.



Material Safety Data Sheet

Material Name: Medium Curing Cutback

Section 12: ECOLOGICAL INFORMATION

There is no information available for the product. Should you have any questions please refer to the contact information in section 1.

Section 13: DISPOSAL CONSIDERATIONS

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations. See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

Section 14: TRANSPORTATION INFORMATION

This product is regulated under TDR:
Shipping Name: UN 1999, Tars, Liquids, 3, PG III
Class: 3
UN number: 1999
Packing Group: III



Section 15: REGULATORY INFORMATION

OSHA/MSHA Hazard Communication:

This product is considered by OSHA/MSHA to be a hazardous chemical and should be included in the employer's hazard communication program.

TSCA: This product and/or its components are listed on the Toxic Substances Control Act (TSCA) inventory.

DSL: The components of this product are listed on the DSL.

WHMIS:

This product is classified as B3, D2A, and D2B under WHMIS criteria and are subject to WHMIS requirements

Section 16: OTHER INFORMATION

Other Information

The information herein is presented in good faith and believed to be accurate as of the effective date given. However, no warranty, expressed or implied, is given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

Key/Legend

EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration.